

关于产品质量指标提升的告知函

Notification Letter on the Improvement of Product Quality Indicators

We adhere to the spirit of Quality First and Customer Foremost and have always been committed to providing high-quality products and services to our customers. We are obligated to continuously improve in order to further enhance the competitiveness of our products, lead the industry development, and meet the needs of customers.

For product quality continuous improvement, the products involved and the improved quality indicators are as follows:

Assembled Roving Products

1. Linear density: The indicator variation for 702 will be improved from $\pm 5\%$ to $\pm 4\%$. After this improvement, all assembled roving products will have a variation of $\pm 4\%$.

Direct Roving Products.

1. Moisture content: The indicator will be improved from $\leq 0.20\%$ to $\leq 0.15\%$.

for 960, 960A and 988A.

2. Breaking strength: The indicator will be improved from $\geq 0.40 \text{ N/ten}$ to

$\geq 0.42 \text{ N/ten}$ for 320, 316HM and 300XF05(E7) and from $\geq 0.40 \text{ N/ten}$ to

$\geq 0.42 \text{ N/ten}$ for 312.

3. ~~Indicator~~ **Indicator**: The ~~indicator~~ **indicator** will be improved from $\pm 5\%$ to $\pm 4\%$

for 320, 316HM and 300XF05(E7) and from $\pm 5\%$ to $\pm 4\%$ for 312.

4. ~~Indicator~~ **Indicator**: The ~~indicator~~ **indicator** will be improved from $\pm 5\%$ to $\pm 4\%$

for 320, 316HM and 300XF05(E7) and from $\pm 5\%$ to $\pm 4\%$ for 312.

5. ~~Indicator~~ **Indicator**: The ~~indicator~~ **indicator** will be improved from $\pm 5\%$ to $\pm 4\%$

Chopped Strand Mat Products

1. ~~Indicator~~ **Indicator**: The ~~indicator~~ **indicator** will be improved from $\pm 5\%$ to $\pm 4\%$

for 320, 316HM and 300XF05(E7) and from $\pm 5\%$ to $\pm 4\%$ for 312.

2. ~~Indicator~~ **Indicator**: The ~~indicator~~ **indicator** will be improved from $\pm 5\%$ to $\pm 4\%$

for 320, 316HM and 300XF05(E7) and from $\pm 5\%$ to $\pm 4\%$ for 312.

3. ~~Indicator~~ **Indicator**: The ~~indicator~~ **indicator** will be improved from $\pm 5\%$ to $\pm 4\%$

for 320, 316HM and 300XF05(E7) and from $\pm 5\%$ to $\pm 4\%$ for 312.

4. ~~Indicator~~ **Indicator**: The ~~indicator~~ **indicator** will be improved from $\pm 5\%$ to $\pm 4\%$

specifications.

Woven Rovings

1. Area weight: The indicator variation will be improved from $\pm 5\%$ to $\pm 4\%$.

2. Moisture content: The indicator will be improved from $\leq 0.10\%$ to $\leq 0.07\%$.

